



Measuring gauge with storage case: includes dial indicator holder, dial indicator, centering piece, and calibrated master.

Function

Using the calibrated master, the distance of the 30 degree clamping slope relative to 1.2 is preset using the dial indicator holder. The tool taper to be measured is placed in the centering piece, allowing the variation of the taper to be measured.

HSK A/C/E	HSK B/D/F	1.6 / JS 10	d 6	Order Number
HSK-A 25	HSK 32	7.21	15	410.230.125.000
HSK-A 32	HSK 40	8.92	19	410.230.132.000
HSK-A 40	HSK 50	11.42	23	410.230.140.000
HSK-A 50	HSK 63	14.13	29	410.230.150.000
HSK-A 63	HSK 80	18.13	37	410.230.163.000
HSK-A 80	HSK 100	22.85	46	410.230.180.000
HSK-A 100	HSK 125	28.56	58	410.230.190.000
HSK-A 125	HSK 160	36.27	73	410.230.192.000
HSK-A 160	-	45.98	92	410.230.196.000

Transatlantic Connection Product Line

Machine Tool Gauges, Tool Changer Alignment, Runout Test Arbors, Clamping Systems, Automatic Tool Holder Grippers, Tool Clamping Components, Pallet Clamping, Cooling and Filtering Systems, Tool Changer Systems, Springs, Brushes, Actuators and Motors, Couplings and Gears, ANY Machine Replacement or Spare Part